Proof of intrinsic safety

For intrinsically safe circuits with a supply.

device: **Jellox Analog xx**

associated equipment:

Manufacturer	Type	Device	EU type examination certificate	ATEX marking
Microtronics	D012-x1***2***05	Rugged GW Analog	SIQ 24 ATEX 212 X	<Ex> II 2G Ex ib IIB T3 Gb

max. output voltage	Uo [V]=	25,6
max. output current	Io [A]=	0,082
max. output power	Po [W]=	0,523
max. external capacity	Co [nF]=	310
max. external inductance	Lo [µH]=	1000

intrinsically safe equipment:

Manufacturer	Type	Device	EU type examination certificate	ATEX marking
VEGA	VEGACAP CP6*.C****Z***	capacitive rod probe	TÜV 04 ATEX 2611 X	<Ex> II 1G oder II 1/2G oder II 2 G EEx ia IIC T6

max. input voltage	Ui [V]=	30	
max. input current	Ii [A]=	0,131	
max. input power	Pi [W]=	0,983	
max. internal capacity	Ci [nF]=	0	n.A.
max. internal inductance	Li [µH]=	0	n.A.

cable + pressure compensation element:

Manufacturer	Type	length [m]
Lapp	Ölflex EB CY 7x0,75	
		274

cable capacitance [nF/m]	0,98
cable inductance [µH/m]:	3,64

resulting cable capacitance	Cc [nF]=	268,52
resulting cable inductance	Lc [µH]=	997,36

safety-related values of the interconnection:

D012-x1***2***05		EGACAP CP6*.C****Z*		Intrinsic safety fulfilled
25,6	**Uo <= Ui**	**30**	V	***YES***
0,082	**Io <= Ii**	**0,131**	A	***YES***
0,523	**Po <= Pi**	**0,983**	P	***YES***
310	**Co >= Ci + Cc**	**268,52**	nF / IIB	***YES***
1000	**Lo >= Li + Lc**	**997,36**	µH / IIB	***YES***

For use in EPL "Gb" (category 2G) and group IIB

Special conditions in the type examination certificate or in the manual of the associated / intrinsically safe equipment must be observed.
The proof of intrinsic safety is based on the safety-related maximum values. These were taken from the manual or the EC type examination certificates for the equipment.

Configuration recommendation:

The recommendation refers to the configuration of your Jellox product. You can make the settings in the platform.
Please refer to the table at **https://support.microtronics.com/jellox-analog/compatible-sensors** for the configuration recommendation.

The recommendation refers to the configuration of your Jellox product. You can make the settings in the platform.

Document revision

version	date	name	change	reason
01v000	26.11.2026	AZ	all	building document

Release

number	date	name	activity	signature
1	26.11.2026	AZ	created	
2			approved	